

- Features:**
- According to JISC 1609 : 1993 AND CNS 5119 general A class specifications.
  - Spectral response close to CIE luminous spectral efficiency.
  - Measuring intensities of illumination in unit of Lux or Foot-candle.(TM-209.TM-209M)
  - Silicon photo diode and filter. • Cosine angular corrected. • Data Hold.

**TM-201L**

**TM-209**

**TM-209M**


## Specifications

	TM-201L LED Light Meter	TM-209 LED Light Meter	TM-209M Multi-LED Light Meter
<b>Light Source</b>	White light LED and all visible light measuring		6 LED light source and all visible light measuring: L0 → Standard light source A. L1 → LED WHITE day light. L2 → LED RED light. L3 → LED AMBER(Yellow) light. L4 → LED GREEN light. L5 → LED BLUE light. L6 → LED PURPLE light. L7~L9 → Default Standard light source A.
<b>Display</b>	3 1/2 digits LED with maximum reading 2000		3 3/4 digits LED with maximum reading 3999
<b>Function</b>	—		Luminous Intensity Measurement
	—		99 records storage capacity
	—		Auto power off with disable function
	Max hold		Max / Min / AVG hold
	Zero adjustment		Real Zero function
	Manual ranging		Auto ranging
<b>Range</b>	200, 2000, 20000, 200000 LUX 20,200, 2000, 20000 FC		40, 400, 4,000, 40,000, 400,000 LUX 40, 400, 4,000, 40,000 FC
<b>Dimension</b>	Meter : 130x55x38mm		
	Sensor : 80x55x25mm		
<b>Weight</b>	250g		
<b>Accuracy</b>	±3% (Calibrated to standard incandescent lamp 2856°K and corrected LED day white light) ±8% (other visible light source)		±3% (Calibrated to standard incandescent lamp 2856°K and corrected LED light source) ±6% (other visible light source)